Entity-Relationship Model Intershop 7

INTERSHOP

Document ID:	ENF7-21-09-01
Version:	7.2.1.0.136
Publication Date:	2012-12-06
Cartridge:	**bc_marketing**
Notes:	DomainID <fk> columns reference to Domain.UUID (core) <pk> = primary key <fk_> = foreign key <ak_> = alternate key <i_> = indexed column <PersistentObject>_AUOWNERID references to <PersistentNUMID>.UUID, see core for detailed column description of _AV tables.

These materials are subject to change without notice. These materials are provided by Intershop Communications AG and its affiliated companies ("Intershop Group") for informational purposes only, without representation or warranty of any kind, and Intershop Group shall not be liable for errors or omissions with respect to the materials. The only warranties for Intershop Group products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

This document and all of its parts are protected by copyright. All rights, including those of duplication, reproduction, translation, microfilming, storage on electronic media and processing in electronic form are expressly reserved.

Intershop® and Enfinity™ are trademarks or registered trademarks of Intershop Communications AG. All other company, product and brand names are trademarks or registered trademarks of their respective owners.

Copyright© 2005-2012 Intershop Communications. All Rights Reserved.

abtest

ABTESTSTATISTICS_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

ABTESTSTATISTICS

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
ABTESTGROUPUUID	VARCHAR2(28 CHAR)	<fk>	<i2>	not null
LASTSTATISTICUPDATE	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

ABTESTSTATISTICS_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

ABTESTGROUP

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
ABTESTUUID	VARCHAR2(28 CHAR)	<fk>	<i2>	not null
CONTROLGROUPFLAG	NUMBER(1,0)			null
RATIO	FLOAT(126)			null
EXTERNALID	VARCHAR2(256 CHAR)			null
USERGROUPID	VARCHAR2(256 CHAR)		<i3>	null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = ABTESTUUID

ABTEST_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

ABTEST

UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
DYNAMICPGID_UUID	VARCHAR2(28 CHAR)	<fk>		null
MAXPARTICIPANTS	NUMBER(21,0)			null
PARTICIPANTRATIO	FLOAT(126)			not null
STARTDATE	TIMESTAMP (9)			not null
ENDDATE	TIMESTAMP (9)			not null
ENABLEDFLAG	NUMBER(1,0)			null
STATUS	NUMBER(11,0)			null
TARGETGROUPID	VARCHAR2(256 CHAR)			null
TARGETGROUPDOMAINID	VARCHAR2(28 CHAR)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = DYNAMICPGID_UUID

ATESTEVENT

ID	NUMBER(21,0)	<pk>	<i>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
DOUBLEVALUE	FLOAT(126)			null
MONEYCODE	VARCHAR2(128 CHAR)			null
MONEYVALUE	NUMBER(38,6)			null
OBJECTTYPE	VARCHAR2(128 CHAR)			null
OBJECTVALUE	VARCHAR2(28 CHAR)			null
PIPELINE	VARCHAR2(128 CHAR)			null
SESSIONID	VARCHAR2(256 CHAR)			null
TYPE	VARCHAR2(128 CHAR)			not null
USERID	VARCHAR2(28 CHAR)			null
ABTESTGROUPUUID	VARCHAR2(28 CHAR)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = ABTESTGROUPUUID

ABTESTGROUP_PA

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
ABTESTGROUPID	VARCHAR2(28 CHAR)	<fk2>	<i3>	not null
PAGELETID	VARCHAR2(28 CHAR)	<fk1>	<i2>	not null
VALIDFROM	TIMESTAMP (9)			null
VALIDTO	TIMESTAMP (9)			null
ONLINEFLAG	NUMBER(1,0)			null
POSITION	FLOAT(126)			not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

abtest.assignment

DYNAMICPGID

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
STARTDATE	TIMESTAMP (9)		<i2>	null
ENDDATE	TIMESTAMP (9)		<i2>	null
ORIGINDESCRIPTION	VARCHAR2(256 CHAR)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

core.pgid

pmc.pagelet

PAGELET

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)		<i2>	not null
PARENTUUID	VARCHAR2(28 CHAR)	<fk>	<i3>	null
VALIDTO	TIMESTAMP (9)			null
VALIDFROM	TIMESTAMP (9)			null
ONLINEFLAG	NUMBER(1,0)			null
AUTHORID	VARCHAR2(28 CHAR)			null
PAGEFLAG	NUMBER(1,0)			null
TEMPLATEFLAG	NUMBER(1,0)			null
ID	VARCHAR2(256 CHAR)		<i2>	not null
DEFINITIONQUALIFIEDNAME	VARCHAR2(256 CHAR)			not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = PAGELETID

UUID = PARENTUUID

UUID = PAGELETUUID

PROMOTION_PA

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
PAGELETUUID	VARCHAR2(28 CHAR)	<fk2>	<i3>	not null
PROMOTIONUUID	VARCHAR2(28 CHAR)	<fk1>	<i2,i3>	not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = PROMOTIONUUID

PROMOTIONORDERASSIGNMENT

ORDERUUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
PROMOTIONUUID	VARCHAR2(28 CHAR)	<pk,fk>	<i1,i2,i3>	not null
USERID	VARCHAR2(28 CHAR)		<i3>	not null
OCA	NUMBER(11,0)			not null

UUID = PROMOTIONID

PROMOTION_AA

PROMOTIONID	VARCHAR2(28 CHAR)	<pk,fk>	<i1,i2>	not null
APPID	VARCHAR2(256 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

promotion.assignment

xcs.product

PRODUCT

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
PRODUCTTYPEID	VARCHAR2(28 CHAR)		<i7>	null
DEFAULTCATALOGCATEGORYID	VARCHAR2(28 CHAR)		<i9>	null
DEFAULTPRODUCTVARIATIONID	VARCHAR2(28 CHAR)		<i8>	null
OFFEREDPRODUCTID	VARCHAR2(28 CHAR)	<fk>	<i10>	null
TYPECODE	NUMBER(11,0)		<i11>	null
SKU	VARCHAR2(256 CHAR)		<i5>	null
MANUFACTURERNAME	VARCHAR2(256 CHAR)		<i12>	null
MANUFACTURERSKU	VARCHAR2(256 CHAR)			null
ONLINEFLAG	NUMBER(1,0)			null
TEMPLATE	VARCHAR2(256 CHAR)			null
IMAGE	VARCHAR2(256 CHAR)			null
THUMBNAIL	VARCHAR2(256 CHAR)			null
MINORDERQUANTITYVALUE	NUMBER(38,6)			null
MAXORDERQUANTITYVALUE	NUMBER(38,6)			null
STEPQUANTITYVALUE	NUMBER(38,6)			null
UNIT	VARCHAR2(256 CHAR)			null
ORIGINALPRODUCTUUID	VARCHAR2(28 CHAR)			null
TAXCLASSID	VARCHAR2(28 CHAR)		<i6>	null
AVAILABLEFLAG	NUMBER(1,0)			null
PRECEQUANTITYVALUE	NUMBER(38,6)			null
VALIDFROM	TIMESTAMP (9)			null
VALIDTO	TIMESTAMP (9)			null
SYNCHRONIZED	TIMESTAMP (9)			null
LASTORDERDATEDB	TIMESTAMP (9)			null
ENDOFLIFEDB	TIMESTAMP (9)			null
DERIVINGDATESFLAG	NUMBER(1,0)			null
AVAILABILITYSTATUS	NUMBER(11,0)			null
PRODUCTVARIATIONPOSITION	FLOAT(126)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null
ATTRIBUTES	CLOB		<i2>	null
NAME	VARCHAR2(1000 CHAR)			null
ATTRIBUTES_DE_DE	CLOB		<i3>	null
NAME_DE_DE	VARCHAR2(1000 CHAR)			null
ATTRIBUTES_EN_US	CLOB		<i4>	null
NAME_EN_US	VARCHAR2(1000 CHAR)			null

UUID = PRODUCTID

UUID = OFFEREDPRODUCTID

ACTIVEPROMOPRODUCTS

PROMOTIONID	VARCHAR2(28 CHAR)	<pk,fk2>	<i>	not null
PRODUCTID	VARCHAR2(28 CHAR)	<pk,fk1>	<i>	not null
OCA	NUMBER(11,0)			not null

UUID = OWNERID

UUID = PROMOTIONID

PROMOTION_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

PROMOTION

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)		<i2>	not null
CAMPAIGNID	VARCHAR2(28 CHAR)	<fk>	<i3>	null
ID	VARCHAR2(256 CHAR)		<i2>	not null
STARTDATE	TIMESTAMP (9)			not null
ENDDATE	TIMESTAMP (9)			not null
RANK	NUMBER(11,0)			null
ENABLEDFLAG	NUMBER(1,0)			null
COUPONCODEREQUIREDFLAG	NUMBER(1,0)			null
UNLIMITEDFLAG	NUMBER(1,0)			null
HASDEFAULTRANKFLAG	NUMBER(1,0)			null
TARGETGROUPID	VARCHAR2(256 CHAR)			null
TARGETGROUPDOMAINID	VARCHAR2(28 CHAR)			null
TYPECODE	NUMBER(11,0)			null
CREATORID	VARCHAR2(28 CHAR)			null
CURRENCYCODE	VARCHAR2(3 CHAR)			null
BUDGETID	VARCHAR2(28 CHAR)			null
BUDGETSOURCEID	VARCHAR2(28 CHAR)			null
BUDGETNOTIFICATIONTHRESHOLD	FLOAT(126)			null
BUDGETNOTIFICATIONEMAIL	VARCHAR2(256 CHAR)			null
DISABLEBYBUDGETFLAG	NUMBER(1,0)			null
SENDMAILIFBUDGETREACHEDFLAG	NUMBER(1,0)			null
SENDMAILIFTHRESHOLDREACHEDFLAG	NUMBER(1,0)			null
USESINGLECODEFLAG	NUMBER(1,0)			null
SINGLECODE	VARCHAR2(256 CHAR)			null
SINGLECODETOTAL	NUMBER(11,0)			null
CODECUSTOMERUNLIMITEDFLAG	NUMBER(1,0)			null
COMBINATION	NUMBER(11,0)			not null
CONTENTACTIVATIONTYPE	NUMBER(11,0)			null
CONTENTACTIVATIONSTARTDATE	TIMESTAMP (9)			null
CONTENTACTIVATIONENDDATE	TIMESTAMP (9)			null
AVAILABLEFLAG	NUMBER(1,0)			null
USECAMPAIGNTIMEFRAMEFLAG	NUMBER(1,0)			null
USECAMPAIGNTARGETGROUPFLAG	NUMBER(1,0)			null
EFFECTDISCOUNTLEVELFLAG	NUMBER(1,0)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

REBATEFILTEROBJECTASSIGNMENT

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
REBATEFILTERGROUPID	VARCHAR2(28 CHAR)	<fk>	<i2>	null
OBJECTID	VARCHAR2(256 CHAR)			null
OBJECTDOMAINID	VARCHAR2(28 CHAR)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = REBATEFILTERGROUPID

REBATEFILTERGROUP

UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
EXCLUSIONFLAG	NUMBER(1,0)			null
FILTEROBJECTTYPE	VARCHAR2(256 CHAR)			null
SCOPE	VARCHAR2(256 CHAR)			null
APPLICATIONUUID	VARCHAR2(28 CHAR)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = REBATEFILTERGROUPID

REBATEFILTERGROUPASSIGNMENT

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
REBATEID	VARCHAR2(28 CHAR)	<fk4>	<i5>	null
REBATEFILTERGROUPID	VARCHAR2(28 CHAR)	<fk2>	<i3>	null
REBATECONDITIONID	VARCHAR2(28 CHAR)	<fk1>	<i2>	null
REBATEACTIONID	VARCHAR2(28 CHAR)	<fk3>	<i4>	null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

PROMOTIONBUDGETSOURC_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCA			
…			

UUID = OWNERID

PROMOTIONBUDGETSOURCE

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
ID	VARCHAR2(256 CHAR)		<i2>	not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

REBATERULEASSIGNMENT

REBATEUUID	VARCHAR2(28 CHAR)	<pk,fk>	<i1,i2>	not null
RULEUUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = REBATEID

UUID = REBATEUUID

UUID = OWNERID

REBATE_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

REBATE

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
PROMOTIONUUID	VARCHAR2(28 CHAR)	<fk>	<i2>	null
CURRENCYCODE	VARCHAR2(3 CHAR)			null
TYPECODE	NUMBER(11,0)			null
POSITION	NUMBER(11,0)			null
CLASSIFICATIONTYPECODE	NUMBER(11,0)			null
CONDOVERRIDEAPPLIEXCLFLAG	NUMBER(1,0)			null
ACTOVERRIDEAPPLIEXCLFLAG	NUMBER(1,0)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = PROMOTIONUUID

PROMOTION_RT

RT_UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
REPLICATIONTARGETID	VARCHAR2(500 CHAR)	<pk>	<i>	not null
LASTREPLICATIONTIME	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

rebate

REBATERESTRICTIONDEFINITION

UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
POSSIBLEAPPLICATIONS	NUMBER(11,0)			null
AFFECTEDOBJECTTYPE	VARCHAR2(256 CHAR)			not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = RESTRICTIONDEFINITIONID

RESTRICTIONDESCRIPTORASSGNMT

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)		<i2>	not null
RESTRICTIONDEFINITIONID	VARCHAR2(28 CHAR)	<fk>	<i3,i5>	not null
DESCRIPTORID	VARCHAR2(256 CHAR)		<i2,i4,i5>	not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

promotion.restriction

REBATECONDITION_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

REBATECONDITION

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
REBATEID	VARCHAR2(28 CHAR)	<fk2>	<i3>	null
PARENTCONDITIONID	VARCHAR2(28 CHAR)	<fk1>	<i2,i4>	null
POSITION	NUMBER(11,0)		<i4>	null
CONDITIONDESCRIPTORID	VARCHAR2(256 CHAR)			not null
NAME	VARCHAR2(256 CHAR)			null
TYPECODE	NUMBER(11,0)			null
NOTFLAG	NUMBER(1,0)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = REBATECONDITIONID

UUID = PARENTCONDITIONID

UUID = REBATEACTIONID

promotion.condition

REBATEACTION_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

REBATEACTION

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
REBATEID	VARCHAR2(28 CHAR)	<fk>	<i2>	not null
ACTIONDESCRIPTORID	VARCHAR2(256 CHAR)			not null
POSITION	NUMBER(11,0)			null
CLASSIFICATION	NUMBER(11,0)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = REBATEID

UUID = REBATEID

promotion.action

AFFILIATESESSION_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

AFFILIATESESSION

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
PROGRAMUUID	VARCHAR2(28 CHAR)	<fk1>	<i2>	null
PARTNERUUID	VARCHAR2(28 CHAR)	<fk2>	<i3>	null
SESSIONID	VARCHAR2(256 CHAR)		<i4>	not null
STARTTIME	TIMESTAMP (9)			null
PROFILEID	VARCHAR2(28 CHAR)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

AFFILIATEPARTNER_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

AFFILIATEPARTNER

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)		<i2>	not null
ID	VARCHAR2(28 CHAR)		<i2,i7>	not null
PARTNERUSERID	VARCHAR2(28 CHAR)		<i3>	null
PARTNERUSERGROUPID	VARCHAR2(256 CHAR)		<i4>	null
PROFILEID	VARCHAR2(28 CHAR)		<i5>	null
ADDRESSID	VARCHAR2(28 CHAR)		<i6>	null
CREATIONDATE	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = PROGRAMUUID

UUID = OWNERID

UUID = PARTNERUUID

AFFILIATEPROGRAM_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

AFFILIATEPROGRAM

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
PARTNERID	VARCHAR2(28 CHAR)	<fk>	<i2,i4>	null
ID	VARCHAR2(28 CHAR)		<i2>	not null
PROGRAMUSERID	VARCHAR2(28 CHAR)		<i5>	null
PROGRAMUSERGROUPID	VARCHAR2(256 CHAR)		<i3>	null
ENABLEDFLAG	NUMBER(1,0)			null
PROGRAMSTART	TIMESTAMP (9)			null
PROGRAMEND	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

AFFILIATESTATISTIC

PARTNERUUID
PROGRAMUUID
SESSIONCOUNT
PROFILECOUNT

affiliatesession

affiliate

BONUSPOINTACCOUNT_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

BONUSPOINTACCOUNT

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
OWNERID	VARCHAR2(28 CHAR)		<i2>	not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

BONUSPOINTENTRY_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = BONUSPOINTACCOUNTUUID

BONUSPOINTENTRY

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
BONUSPOINTACCOUNTUUID	VARCHAR2(28 CHAR)	<fk>	<i2>	not null
EXPIRATIONDATE	TIMESTAMP (9)			null
USEDVALUE	NUMBER(38,6)			not null
VALUE	NUMBER(38,6)			not null
REDEEMABLEFLAG	NUMBER(1,0)			null
REFERENCE	VARCHAR2(256 CHAR)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

bonuspoint

UUID = CAMPAIGNID

CAMPAIGN_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCALEID			
…			

UUID = OWNERID

CAMPAIGN

UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
STARTDATE	TIMESTAMP (9)			not null
ENDDATE	TIMESTAMP (9)			not null
ENABLEDFLAG	NUMBER(1,0)			null
FINISHEDFLAG	NUMBER(1,0)			null
TARGETGROUPID	VARCHAR2(256 CHAR)			null
TARGETGROUPDOMAINID	VARCHAR2(28 CHAR)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

CAMPAIGN_RT

RT_UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
REPLICATIONTARGETID	VARCHAR2(500 CHAR)	<pk>	<i>	not null
LASTREPLICATIONTIME	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

campaign

UUID = PROMOTIONUUID

PROMOTIONNOTE

UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
DOMAINID	VARCHAR2(28 CHAR)			not null
BASICPROFILEUUID	VARCHAR2(28 CHAR)	<fk2>		null
PROMOTIONUUID	VARCHAR2(28 CHAR)	<fk1>		null
NOTE	CLOB			null
CREATIONDATE	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = BASICPROFILEUUID

promotion.note

PROMOCODEGRPCHANNELASSIGNMENT

PROMOCODEGROUPUUID	VARCHAR2(28 CHAR)	<pk,fk>	<i1,i2>	not null
CHANNELDOMAINID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = PROMOCODEGROUPUUID

PROMOCODEGROUPPROMOASSIGNMENT

PROMOCODEGROUPUUID	VARCHAR2(28 CHAR)	<pk,fk1>	<i1,i2>	not null
PROMOTIONUUID	VARCHAR2(28 CHAR)	<pk,fk2>	<i1>	not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

PROMOTIONCODEORDERASSIGNMENT

ORDERUUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
PROMOTIONCODEUUID	VARCHAR2(28 CHAR)	<pk,fk>	<i1,i2,i3>	not null
USERID	VARCHAR2(28 CHAR)		<i3>	not null
OCA	NUMBER(11,0)			not null

UUID = PROMOCODEGROUPUUID

UUID = OWNERID

PROMOTIONCODEGROUP_AV

OWNERID	…	<pk,fk>	not null
NAME			
LO			
…			

PROMOTIONCODEGROUP

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)		<i2>	not null
ID	VARCHAR2(256 CHAR)		<i2>	not null
CODEQUANTITY	NUMBER(11,0)			null
USEPROMOTIONTIMEFLAG	NUMBER(1,0)			null
STARTDATE	TIMESTAMP (9)			null
ENDDATE	TIMESTAMP (9)			null
ENABLEDFLAG	NUMBER(1,0)			null
USEPROMOTIONTARGETGROUPSFLAG	NUMBER(1,0)			null
NUMBEROFREUSES	NUMBER(11,0)			null
NUMBEROFREUSESPERCUSTOMER	NUMBER(11,0)			null
CREATECODEQUANTITY	NUMBER(11,0)			null
USEPROMOTIONAPPSFLAG	NUMBER(1,0)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

PROMOTIONCODEGROUP_RT

RT_UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
REPLICATIONTARGETID	VARCHAR2(500 CHAR)	<pk>	<i>	not null
LASTREPLICATIONTIME	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = PROMOTIONCODEUUID

UUID = PROMOTIONCODEGROUPID

UUID = OWNERID

PROMOTIONCODE_AV

OWNERID	…	<pk,fk>	not null
NAME			
LOCA			
…			

PROMOTIONCODE

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)		<i2>	not null
PROMOTIONCODEGROUPID	VARCHAR2(28 CHAR)	<fk>	<i3>	null
CODE	VARCHAR2(256 CHAR)		<i2>	not null
SECUREDFLAG	NUMBER(1,0)			null
STATUS	NUMBER(11,0)			not null
REDEMPTIONDATE	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

UUID = PROMOTIONCODEGROUPID

PROMOTIONCODEGROUP_AA

PROMOTIONCODEGROUPID	VARCHAR2(28 CHAR)	<pk,fk>	<i1,i2>	not null
APPID	VARCHAR2(256 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

PROMOTIONCODE_RT

RT_UUID	VARCHAR2(28 CHAR)	<pk>	<i>	not null
REPLICATIONTARGETID	VARCHAR2(500 CHAR)	<pk>	<i>	not null
LASTREPLICATIONTIME	TIMESTAMP (9)			null
OCA	NUMBER(11,0)			not null
LASTMODIFIED	TIMESTAMP (9)			not null

code

BASICPROFILE

UUID	VARCHAR2(28 CHAR)	<pk>	<i1>	not null
DOMAINID	VARCHAR2(28 CHAR)	<ak>	<i2,i8>	not null
DEFAULTADDRESSID	VARCHAR2(28 CHAR)		<i4>	null
ANNIVERSARY	VARCHAR2(256 CHAR)			null
BIRTHDAY	VARCHAR2(32 CHAR)			null
BIRTHDAYDATE	TIMESTAMP (9)			null
COMPANYNAME	VARCHAR2(256 CHAR)			null
DESCRIPTION	VARCHAR2(256 CHAR)			null
FIRSTNAME	VARCHAR2(256 CHAR)		<i3>	null
COMPANYNAMETRANSCRIPTION	VARCHAR2(256 CHAR)			null
FIRSTNAMETRANSCRIPTION	VARCHAR2(256 CHAR)			null
GENDER	VARCHAR2(32 CHAR)			null
HOBBIES	VARCHAR2(256 CHAR)			null
HONORIFIC	VARCHAR2(256 CHAR)			null
JOBTITLE	VARCHAR2(256 CHAR)			null
KEYWORDS	VARCHAR2(256 CHAR)			null
LASTNAME	VARCHAR2(256 CHAR)		<i5>	null
LASTNAMETRANSCRIPTION	VARCHAR2(256 CHAR)			null
NICKNAME	VARCHAR2(256 CHAR)			null
PREFERREDLOCALE	VARCHAR2(10 CHAR)			null
PREFERREDCURRENCY	VARCHAR2(10 CHAR)			null
PREFERREDTIMEZONEID	VARCHAR2(256 CHAR)			null
PROFESSION	VARCHAR2(256 CHAR)			null
SECONDLAST